

THERMAL/THERMAL TRANSFER BAR CODE PRINTER

RING 400PEI+SERIES



ALL MIGHTY DESK TOP PRINTER

- Experienced design makes it sharp and friendly
- 203/300DPI
- 152MM/SEC
- 32 BIT RISC CPU
- 16MB SDRAM, 8MB FLASH
- VARIOUS OPTION

RING 400PEI+Series Specification

Model Name	408PEIL+	408PEI+	412PEI+
Print Speed	101.6mm / sec	152.4mm / sec	101.6mm / sec
Resolution	203dpi	203dpi	300dpi
Print Width	108.0mm	108.0mm	105.7mm
Print Length	4~1727mm	4~1727mm	4~726mm
Print Method	Thermal Transfer / Direct Thermal		
Media Type	Roll Stock (continuous or die cut), Fan Fold, Tag Stock		
Media Width	25mm to 118mm		
Media Thickness	0.06~0.25mm		
Supply Roll Maximum Diameter	127.0mm		
Ribbon	Ink face-out		
Ribbon width	30mm to 110mm		
Ribbon Length	300M		
Ribbon Roll Diameter	Industry standard : 25.4mm core diameter, Maximum diameter of 68mm		
Processor	32bit RISC CPU		
Memory	16MB SDRAM, 8MB Flash		
Sensor	Die-cut label home position, black mark, no ribbon, no media		
Printer Language	ALL, RZPL		
Resident Font	11 resident Windows bit mapped font. Scalable font in 4 orientations.		
Font Download	Windows Bitmap fonts and Asian fonts		
Barcodes and 2D codes	Code 39, Code 93, Code 128(Sub set A, B, C), UCC128, UCC/EAN-128, UPC A/E(add on 2&5), Interleaved 2 of 5, EAN128,EAN8/13(add on 2&5), Codebar, PostNET, DUN14, MaxiCode, HIBC, Plessey, RPS128, PDF417, Datamatrix, QR code		
Graphics	BMP, PCX, and down loadable formats		
Interfaces	USB2.0	USB2.0, Ethernet, Serial	
Operation Panel	2 colored LEDs , 1 Function key		
Cabinet	Durable plastic with Black transparent media window		
Power supply	Auto Switching 100-240VAC, 50/60Hz		
Operating Temperature	5 to 40 centigrade		
Humidity	30 to 85%, non-condensing		
Approval	CE(EMC), FCC Class A, CCC, BIS, CB, CUL, BSMI		
Dimensions	171mm H x 226mm W x 285mm D		
Weight	2.7Kg		
Options	Rotary cutter Stripper Module CF Card Adapter with RTC External Label Stocker External Label Rewinder		

THE ABOVE IS FOR INFORMATION ONLY.

Autonics Company limited reserves the right to change specifications without notice.

Autonics Co., Ltd.

4-14-26 Shimomuneoka Shiki-shi
Saitama 3530008 Japan
www.ringprinter.com
sales@autonics.co.jp

